



Aviation Devices & Electronic Components, L.L.C.  
Phone: 817-738-9161

Document IS-AG-020  
Revision \_B\_  
Date: 01-12-17  
Page 1 of 3

---

## INSTALLATION INSTRUCTIONS

---

### Av-DEC® Non-Conductive Gasket Installation

**NOTE: Read this specification completely before antenna installation.**

#### 1. SCOPE

This specification describes the method for antenna and aircraft surface preparation and antenna installation using the Av-DEC® HI-TAK® Polyurethane Non-Conductive Polyurethane Gasket, HT3326-5 Self-Leveling Green® sealant, and HI-TAK® Polyurethane StretchSeal™ tape. This method is to be used only for non-conductive antenna gasket installations.

#### 2. APPLICABLE DOCUMENTS

Engineering orders, aircraft maintenance manual, avionics installation manual, and/or user maintenance manual as applicable.

#### 3. REQUIREMENTS


**3.1 MATERIALS - Cleaning Solvent** - Isopropyl alcohol or other approved cleaning solvent.

**3.2 SURFACE PREPARATION** - Inspect faying surface areas that will contact the Av-DEC® gasket materials for corrosion and take corrective action based upon current maintenance manual requirements. Remove any previously applied adhesives, sealants or fillet sealing materials. Ensure any primer and paint is fully cured before proceeding. Surfaces that will come in contact with the Av-DEC® gasket material shall be wiped with a clean, solvent dampened cloth, followed immediately by wiping with a clean dry cloth to remove any remaining paint, dust, oil, grease, fingerprints, and other contamination prior to the Av-DEC® gasket material installation.

**3.3 GASKET INSTALLATION** - Av-DEC® HI-TAK® Non-Conductive Polyurethane Gaskets are supplied with protective release film on both sides of the gasket. Leave release film in place until ready to install gasket. Remove gasket from the protective packaging, taking care not to fold or bend it. Verify that fastener holes and connector cutouts in the gasket will align with the antenna when positioned for installation. Trim the perimeter of the gasket flush with the antenna if needed. Remove release film from the side of the gasket marked "antenna side" and position gasket over the antenna. Beginning at one side or corner of the antenna, place gasket into position, carefully aligning gasket fastener holes with antenna fastener holes. Release film should remain on exposed "aircraft side" of gasket until immediately prior to antenna installation.

## INSTALLATION INSTRUCTIONS

**Figure 1 Typical HI-TAK® Non-Conductive Antenna Gasket Installation with HT3326-5 Self-Leveling Green® Sealant and StretchSeal™ Tape**



**StretchSeal™ Tape on connector**  
**HI-TAK® Antenna Gasket in place on antenna**  
**HT3326-5 Self-Leveling Green® Sealant applied to connector base**

**3.4 SEALING ANTENNA CONNECTOR BASE** - A major source of antenna corrosion occurs from moisture leakage into the base of the antenna connector. Although the antenna can be mounted with only the sealed antenna gasket installed, Av-DEC® highly recommends the application of HT3326-5 Self-Leveling Green® sealant to the connector mounting area. HT3326-5 sealant will prevent moisture ingress through the connector base.

**Do not open HT3326-5 package until ready for use. Follow instructions for priming and mixing on the HT3326-5 cartridge. Dispose of cartridge if it has been removed from package for more than 24 hours.**

Apply a layer of Av-DEC® HT3326-5 Self-Leveling Green® sealant (following enclosed application instructions) to the antenna-mounting surface of the antenna connector, as shown in Figure 1. Allow the sealant to cure before mounting the antenna on the aircraft.

**3.5 SEALING ANTENNA CONNECTOR** - An additional source of corrosion occurs from moisture leakage into the antenna connector. Although the antenna can be mounted with only the sealed antenna gasket installed, Av-DEC® highly recommends the application of HI-TAK® Polyurethane StretchSeal™ (EN110589 or AD89513) tape over the connector. StretchSeal™ tape will prevent moisture ingress into the connector.



---

## INSTALLATION INSTRUCTIONS

---

To apply the StretchSeal™ tape, remove the tape from the package and unroll a small length of tape. Wrap the StretchSeal™ Tape around the mated connector with a 50% overlap while stretching the tape 25% to 50% to ensure a tight wrap. A tight wrap is necessary to ensure a proper seal. Coverage shall be from the base of the antenna to at least ½” beyond the connector and onto the insulation jacket of the coaxial cable.

Note: Aircraft cutout hole must be at least ¼” greater in diameter than the connector outer diameter when using StretchSeal™ tape.

Apply cable ties immediately above and below the mated connector and the free end of tape.

- 3.6 ANTENNA INSTALLATION** - Remove release film from the “aircraft side” of the gasket. Pre-position at least two fasteners through the antenna and gasket. Align fasteners at correct locations on the aircraft surface. Tighten each fastener one to two turns to hold the antenna in place on the aircraft. Install remaining fasteners through the antenna and gasket. Tighten fasteners in accordance with approved maintenance manual procedures. Wait at least 15 minutes and retighten the fasteners.
- 3.7 FILLET SEAL** - Fillet sealing is not required, or needed, with Av-DEC® antenna gaskets. However, a fillet seal may be used along with the gasket if required by maintenance or installation documentation.
- 4. MAINTENANCE** - Installation of the Av-DEC® HI-TAK® Non-Conductive Polyurethane Gaskets, HT3326-5 Self-Leveling Green® sealant and StretchSeal™ tape requires no additional maintenance tasks than those already specified in the approved maintenance manual procedures. Av-DEC® recommends replacing the Av-DEC® HI-TAK® Non-Conductive Polyurethane Gasket, HT3326-5 Self-Leveling Green® sealant and StretchSeal™ tape each time the antenna is removed from the aircraft.
- 5. GASKET REMOVAL** - After removing antenna fasteners, use a phenolic or wooden tool as a wedge between the antenna and aircraft surface to separate antenna from the aircraft. After the antenna is removed, cut the cable ties from the connector wrap (if present) and remove StretchSeal™ tape. Disconnect aircraft coax cable(s) and peel antenna gasket from aircraft. Remove Self-Leveling Green® sealant from the antenna. Use isopropyl alcohol or other approved cleaning solvent to remove any remaining residue.
- 6. GASKET REPLACEMENT** - Av-DEC® recommends the antenna gasket be replaced each time the antenna is removed. If a replacement gasket is not available, carefully remove the antenna, taking care not to damage the gasket.